

Southwest Research InstituteTM

CLEANER MARINE ENGINES - CAN IT BE DONE?

Presentation to Carbon Monoxide Workshop

by

James N. Carroll Southwest Research Institute March 24, 2003



Background What's Going On?

Both EPA and CARB are developing emission regulations to cover sterndrive and inboard (SD/I) SI marine engines

CARB SD/I rule adopted at Board hearing on July 26, 2001

standards supported by marine industry

July 25, 2002 EPA NPRM proposes evaporative standards for SI marine engines

 Not planning exhaust emission standards until more information available about catalyst application in the marine environment

What Technologies Can Potentially Be Applied to SD/I Engines?

Electronic fuel injection (EFI)

Stoichiometric or low-emissions calibrations

- requires exhaust gas oxygen (EGO) sensor

Exhaust gas recirculation (EGR)

reduces NOx emissions

Aftertreatment - catalysts

reduce HC, CO, and NOx

Marine Engine Catalyst Application Issues

Safety - Under-Deck Temperatures

- Potential for catalyst to overheat
- Spec. is 200 F max. surface temperature
- Can this be adequately protected against?

Safety - Exhaust Leaks

Additional connections and components provide additional opportunities for leaks

Durability - Can ceramic components survive marine environment?

- Water can quickly destroy hot ceramic components
 Potential Safety Benefit
 - Reduction or elimination of CO danger behind boats

What's Been Done So Far?

SwRI has performed two projects for CARB and EPA to demonstrate the potential for cleaner SD/I engines "Catalytic Reduction of Marine Sterndrive Engine Emissions"

- Applied EGR and catalyst to marine V-8 engine
- Determined effects on engine performance and emissions
- Identified 2 systems capable of reducing HC+NOx emissions by 80%

"Marine Exhaust System Modifications"

- Investigated water reversion problem
- Proposed several modifications to exhaust system design
- Tested modified systems in a boat on a lake
- Virtually eliminated reversion using heated manifold concept

SwRI SD/I Research Project

Objective: Determine level of emission reduction achievable on typical SD/I engine Approach: Apply EGR and catalyst technology to Mercury Marine 7.4L V-8

- install in test cell
- take performance and emissions data



Best Configurations

Riser Catalysts

- expanded exhaust passage to reduce back pressure with same external dimensions as stock Mercury riser
- 80% reduction in HC+NOx
- 50% reduction in CO

Expanded Elbow Catalyst

- allows catalyst use without increasing height or width
- designed to prevent water reversion
- 75% reduction in HC+NOx
- 50% reduction in CO





"Marine Exhaust System Modifications"

Project performed by SwRI for CARB

Objective:

investigate water reversion problem and propose possible solutions

Approach:

- study marine engine water reversion in boat on a lake using industry-specified test procedures
- formulate modifications to exhaust system design
- apply modifications in boat and test to determine effectiveness

On-Lake Testing

Instrumented 4.3 L V-6 in Sea Ray 190 boat Performed on-water testing to study water reversion

- NMMA Recommended Test Modes
- SwRI Added Test Modes

Accumulated water seemed to be caused more by condensation than reversion

Developed exhaust system modifications to reduce exhaust system condensation

Modifications effective in protecting catalyst and oxygen sensor

"Development of Low Emissions SD/I Boats" SwRI Project for CARB

Objectives:

- Develop catalytic marine exhaust systems
- Demonstrate durability of these systems in boats on the water

Primary Tasks:

- Develop stoichiometric marine engine calibrations
- Design and fabricate 4 catalytic marine exhaust systems
- Install systems in 4 boats
- Perform on-water durability
- Evaluate performance and durability of the emission reduction systems

Current Project Status

Project started ~ mid-August

Boats shipped to SwRI

Catalysts designed and shipped by MECA member companies

Catalyzed exhaust manifolds being fabricated

Communication with Coast Guard Auxiliary

Emissions calibration work ongoing

Procuring instrumentation for on-water activities

Durability of Low-Emissions Small Off-Road Engines

Project Background

CARB planning further reductions in emission standards for small off-road engines (SORE)

Catalyst technology could be required to meet future standards

Questions remain about the durability of catalysts applied to small off-road engines

Objective

Demonstrate durability of catalyst application to small off-road engines

 Emissions target is 50% of engine 0-hour baseline HC+NOx emissions at either 250 hours (Class 1 engines) or 500 hours (Class 2 engines)

Development of Low-Emissions Engines

Perform baseline, 6-mode emission tests, as received Install catalysts and develop low-emissions calibrations

- Adjust A/F calibrations, as required
- Consider use of supplemental air

Emission test developed engines

obtain pre- and post-catalyst data

Install evaporative emission control technologies on two engines

- Low-permeability fuel tank and line
- Measure evaporative emissions in baseline and low-evaporative configurations

Durability Testing

Durability to be performed using repetitive 6-mode cycles (Cal. Phase II RFG)


Class 1 engines:

- 250 hours total
- Emission tests at 125 and 250 hours

Class 2 engines:

- 500 hours total
- Emission test at 125, 250, and 500 hours

Small Offroad Engine #1



Current Approaches To CO Reduction

Lean Engine Operation

- LPG Fuel
 - Lift trucks, floor waxers, Zamboni
- Diesel Fuel
 - Gen sets, marine propulsion

Closed -Loop Control

- Stoichiometric operation with catalysts
- Large spark-ignited engines (>25hp)
- Gen sets, lift trucks, airport ground support, man lifts, pumps

Development of Four-Stroke Outboard Engines

Challenges

Small Offroad Engines (<25hp)

Engine thermal durability, catalyst durability, costs of catalytic mufflers

Large Spark-Ignited Engines (>25hp)

Commercially available

Marine Propulsion Engines

- Packaging catalyzed exhaust
- Durability of catalyst and EGO sensor
- Development of closed-loop control calibrations

Questions?

